

TEXOL ULTRA MAX

SAE 0W20 API SP



JV of: **gandhar**
oil refinery (india) ltd.

Product Description

Texol® Ultra Max 0W20 API SP is a fully synthetic oil formulated with a balanced additive component system designed to deliver outstanding engine protection. It meets and exceeds the industry's toughest standards and requirements. It provides protection against the potential for pre-ignition in the (TGDI) engine. Fully meets the requirements of the ILSAC GF-5, API SP and GM: dexos1 Gen 3 specifications.

Applications

Texol® Ultra Max 0W20 SP is designed to use in modern gasoline powered engines, turbo charged engines and multi-valve injected engines.

Features and Benefits

- Delivers enhanced performance in the areas of wear protection, piston cleanliness, and fuel economy.
- Delivers quick cold starts with outstanding low-temperature Properties.
- Reduces the friction to maximize the horsepower.
- High Resistance to oil degradation.
- Provides Turbocharger cleanliness and Turbo coolant temp control

Specifications and Approvals

- GM: dexos1 Gen 3
- API: SP
- ILSAC: GF-5

Characteristics

Key Properties	Test Methods	Specification	Typical Value
SAE Grade	---	SAE 0W20	---
Kinematic Viscosity @ 40°C	ASTM D445	---	43.65
Kinematic Viscosity @ 100°C	ASTM D445	6.9 to 9.3	8.363
Viscosity Index	ASTM D2270	140 Min	171
CCS @ -35°C	ASTM D5293	6,200 Max	5,600
Pour Point, °C	ASTM D97	(-) 39 Max	(-) 42
Base Number	ASTM D2896	6.0 Min	8.3
Flash Point, °C	ASTM D92	190 Min	216

Health and Safety

Detailed health and safety information for this product is provided in a Material Safety Data Sheet which is available upon request from our Texol sales office.