

TEXOL ULTRA MAX

SAE 5W30 API SN



Powered By
gandhar
 oil refinery (india) ltd.

Product Description

Texol® Ultra Max SAE 5W30 API SN is a fully synthetic, energy-efficient Passenger Car Motor Oil, made with high quality hydro-cracked & hydro-treated base oils and additives with proven performance. The base oils provide excellent lubricity and oxidation resistance. The engine oil provides wide temperature range operability.

Applications

Texol® Ultra Max SAE 5W30 API SN is a fully synthetic engine oil designed for use in modern gasoline engines, passenger cars, SUVs, vans and light trucks. American and Japanese cars following API & ILSAC specifications oils widely use this type of engine oil.

Characteristics

Features and Benefits

- High temperature deposit protection for pistons.
- Easy Cold starting and Sludge Control.
- Seal Compatibility.
- Fuel economy
- Turbocharger protection
- Compatible with emission control systems.

Specifications and Approvals

- API-SN
- ILSAC GF-5

Key Properties	Test Methods	Specification	Value
API	---	SN	---
SAE Grade	---	SAE 5W30	SAE 5W30
Kinematic Viscosity @ 40°C	ASTM D445	---	55.25
Kinematic Viscosity @ 100°C	ASTM D445	9.3 to 12.5	10.10
Viscosity Index	ASTM D 2270	130 Min	173
CCS @ -30°C	ASTM D5293	6,600 Max	5,700
Pour Point, °C	ASTM D97	(-) 33 Max	(-) 42
Base Number	ASTM D 2896	6.0 Min	7.3
Flash Point, °C	ASTM D92	186 Min	220

Health and Safety

Detailed health and safety information for this product is provided in a Material Safety Data Sheet which is available upon request from our Texol sales office.