

TEXOL ULTRA S

SAE 10W40 API SN



Powered By
gandhar
oil refinery (india) ltd.

Product Description

Texol® Ultra S SAE 10W40 is an advanced, semi-synthetic engine oil meeting the requirements of almost all the engines in passenger cars running on multiple fuels like Gasoline, Bio Diesel, Gasoline-ethanol Mix, LPG & NG. It is mainly suited for turbo charged, multi valve and direct injection engines, based on OEM recommendation.

Applications

They are semi-synthetic engine oils designed for use in modern gasoline engines, diesel engines (without particulate filters) and gas engines of model year 2012 and later. And it is also suitable for use with bio diesel and Gasoline – Ethanol blends.

Features and Benefits

- As a Semi synthetic engine oil, it provides excellent oxidation stability and low temperature flow properties.
- Protection of three-way catalyst poisoning by reducing the volatility of the phosphorus in the lubricant.
- Helps to protect the engine throughout the oil drain interval helps to protect high performance engines from power and performance robbing deposits.

Specifications and Approvals

- API-SN

Characteristics

Key Properties	Test Methods	Specification	Value
API	---	SN	---
SAE Grade	---	SAE 10W40	SAE 10W40
Kinematic Viscosity @ 40°C	ASTM D445	---	90.27
Kinematic Viscosity @ 100°C	ASTM D445	12.5 – 16.3	13.72
Viscosity Index	ASTM D2270	120 Min	155
CCS @ -25°C	ASTM D5293	7,000 Max	5,600
Pour Point, °C	ASTM D97	(-) 21 Max	(-) 42
Base Number	ASTM D2896	6.8 Min	7.3
Flash Point, °C	ASTM D92	216 Min	224

Health and Safety

Detailed health and safety information for this product is provided in a Material Safety Data Sheet which is available upon request from our Texol sales office.