

TEXOL ULTRA X

SAE 20W50 API SL



Powered By
gandhar
oil refinery (india) ltd.

Product Description

Texol® Ultra X SAE 20W50 API SL is a mineral oil type energy-efficient Passenger Car Motor Oil; made with high quality solvent refined base oils with additives of proven performance. The base oils provide excellent lubricity and oxidation resistance. The engine oil provides wide temperature range operability.

Applications

Texol® Ultra X SAE 20W50 API SL is a mineral oil type engine oil designed for use in modern gasoline engines, passenger cars, SUVs, vans and light duty trucks under OEM's maintenance service. American cars following API specification widely use this type of engine oil.

Features and Benefits

- High temperature deposit protection for pistons.
- Sludge Control.
- Seal Compatibility.
- Fuel economy.
- Turbocharger protection.

Specifications and Approvals

- API SL
- API CF

Characteristics

Key Properties	Test Methods	Specification	Value
API	---	SL	---
SAE Grade	---	SAE 20W50	SAE 20W50
Kinematic Viscosity @ 40°C	ASTM D445	---	164.5
Kinematic Viscosity @ 100°C	ASTM D445	16.3 to 21.9	19.27
Viscosity Index	ASTM D2270	120 Min	134
CCS @ -15°C	ASTM D5293	9,500 Max	6,400
Pour Point, °C	ASTM D97	(-) 18 Max	(-) 27
Base Number	ASTM D2896	7.3Min	7.5
Flash Point, °C	ASTM D92	200 Min	224

Health and Safety

Detailed health and safety information for this product is provided in a Material Safety Data Sheet which is available upon request from our Texol sales office.