
# TEXOL ATF



# **Product Description**

TEXOL® ATF CVT Fluid is an ultra-premium, fully synthetic automatic transmission fluid designed to service most CVT equipped vehicles. TEXOL CVT Fluid is recommended for use in virtually all chain and belt driven CVT transmissions. This product provides engineered anti-shudder performance for smooth transfer of power in highly sophisticated variable drive transmissions found in many latest cars and SUVs. TEXOL CVT Fluid provides outstanding, long-term service by providing exceptional anti-oxidation and anti-wear protection.

# **Applications**

TEXOL® ATF CVT is a high-performance transmission oil formulated with selected synthetic base stocks and specially recommended for use in Continuously Variable Automatic Transmissions (CVT). It has been recommended to be used in most CVT transmissions of various brands.

### **Features and Benefits**

- Good viscosity/temperature characteristics.
- High thermal stability.
- Very good low temperature properties.
- High stability to aging and high chemical resistance.
- Resistance to wear and good friction characteristics.
- Excellent corrosion protection.

# **Quality, Specifications and Approvals**

- Audi Chain G-052-180-A2
- Honda Push Belt HCF 2
- Nissan Push Belt NS 2
- Subaru Chain CVTF Lineartronic
- Toyota Push Belt CVTF FE

## Characteristics

Key Properties	Test Methods	Specification	Value
Density @ 15°C	ASTM D4052		0.85
Brookfield Viscosity @ (-) 40°C	ASTM D2983	15,000 Max	12,300
Kinematic Viscosity @ 40°C	ASTM D445		32.3
Kinematic Viscosity @ 100°C	ASTM D445	5 - 8	7
Viscosity Index	ASTM D2270	145 Min	187
Flash Point °C	ASTM D92	160 Min	175
Pour Point °C	ASTM D97	(-) 35 Max	(-) 45

# **Health and Safety**

Detailed health and safety information for this product is provided in a Material Safety Data Sheet which is available upon request from our Texol sales office.