

TEXOL ATF

Dex III



Powered By
gandhar
 oil refinery (india) ltd.

Product Description

Texol®ATF Dex III a very high-performance automatic transmission fluid (ATF) designed to provide good performance in a wide variety of new types of transmissions in service and commercial vehicles. It is also designed to perform well in specified hydraulic systems. It is made using very highly refined base oils and additives such as viscosity index improvers, antioxidants and friction modifiers. Even in older engines with Manual Transmissions, it is also used as a power steering fluid.

Applications

Texol ATF Dex III is recommended for earlier models passenger cars and light truck automatic transmissions. It is also used in power steering systems and hydraulics of farm equipment.

Features and Benefits

- Good viscosity/temperature characteristics.
- High thermal stability.
- Very good low temperature properties.
- High stability to aging and high chemical resistance.
- Resistance to wear and good friction characteristics.
- Excellent corrosion protection.

Quality, Specifications and Approvals

- GM DEX III

Characteristics

Key Properties	Test Methods	Specification	Typical Value
API	--	Dexron III	---
Brookfield Viscosity, (-) 40 °C	ASTM D2983	20,000 Max	14,000
Kinematic Viscosity @ 40°C	ASTM D445	---	34.3
Kinematic Viscosity @ 100°C	ASTM D445	5 - 8	7.3
Viscosity Index	ASTM D2270	140	186
Flash Point °C	ASTM D92	170 Min	212
Pour Point °C	ASTM D97	(-) 21 Max	(-) 36

Health and Safety

Detailed health and safety information for this product is provided in a Material Safety Data Sheet which is available upon request from our Texol sales office.